

Newhouse Industrial Estate  
Motherwell, Scotland ML1 5RX  
Tel: 01698 735 700  
Fax: 01698 832 861  
Email: info@antonine-inks.co.uk

Manchester Branch  
Tel: 01942 521 340  
Dispensing Division  
Tel: 01558 824 618

Antonine Inks Europe - Belgium  
Tel: +32 (0) 476 515 175

[www.antonine-inks.co.uk](http://www.antonine-inks.co.uk)



**antonine** PRINTING  
INKS LTD

## DOLPHIN

- Fully pigmented
- Clean running at high and low speeds
- Low foaming characteristics
- Good commercial light fastness
- Economy of use
- Non-flammable
- Non-toxic

Waterbased Flexographic inks and varnishes are formulated for printing pre / post print corrugated cases, kraft multiwall sacks and various other paper products. They are suitable for pre-printers, printer-tubers and printer-slotter units due to their excellent clean printing properties.

**Reduction** to press viscosity is done by adding water only.

**Press Viscosity** is determined to some extent by colour and design, anilox roller, screen and machine speed. This can be As low as 17" Zahn 2 and as high as 35" Zahn 2 when printing.

**Slip Resistance** can be formulated to suit requirements during filling, storing and transportation. The co-efficient of friction can be easily adjusted up to 40° slip angle.

**Foaming** can be a problem with some ink circulation system and although DOLPHIN inks are formulated to minimise foaming, a small addition of antifoam in such cases will normally cure foam build ups.

The complete Colour Range of DOLPHIN inks can be supplied, be it a standard colour, pantone matching or a specialist matching.