

Newhouse Industrial Estate
Motherwell, Scotland ML1 5RX
Tel: 01698 735 700
Fax: 01698 832 861
Email: info@antonine-inks.co.uk

Manchester Branch
Tel: 01942 521 340

Dispensing Division
Tel: 01558 824 618

Antonine Inks Europe - Belgium
Tel: +32 (0) 476 515 175

www.antonine-inks.co.uk



antonine PRINTING
INKS LTD

SPECTRUM

- Fully pigmented
- Clean running at high and low speeds
- Light fastness can be designed to meet requirements
- Chemical resistance if required
- Non - Flammable
- Non - Toxic
- Excellent water resistance when dry
- Excellent rub resistance
- Easily modified to give heat resistance up to 250° C

Inks are fully pigmented, water based and can be adapted to print on paper, clay coated paper, poly coated paper, treated polythene, foil and various polypropylene films. Chemical resistance properties can be incorporated into the inks.

Reduction is made by water only.

Press Viscosity is determined to some extent by colour and design, anilox roller screen and machine speed.

This can be as low as 17" Zahn 2 and high as 35" Zahn 2 when printing slowly.

Product Resistance if required e.g : for fertiliser or soap, should be specified when ordering to enable correct pigment selection.

Chemical Resistance can be incorporated into the ink, if required. This family of inks can be designed to resist fertiliser, acid, alkali and many other products.

Foaming can be a problem with some ink circulation systems and although SPECTRUM inks are formulated to minimise foaming, a small addition of antifoam in such cases will normally cure foam build ups.

The complete Colour Range of SPECTRUM inks can be supplied be it a standard colour, Pantone matching or a specialist matching.